

# SAMCEN

*Ideas For Communication*

## Fully Digital Discussion Unit

SCS-6050C SCS-6050D



### Products picture



SCS-6050C



SCS-6050D

### Specifications

Model	SCS-6050C/D
Power supply	DC24V supplied by the control host
Intercommunication	DIN 8-pole
Power consumption	3W
Loudspeaker power	1.2W
Transducer type	Electret condenser
Directional pattern	Cardioid
SNR	> 80dB
Crosstalk attenuation	at 1k Hz > 80dB
Distortion	<0.10%
Frequency response	60~12KHz
Equivalent noise	≈20dB SPL
Maximum SPL	105dB(3% threshold)
Sensitivity	-22dBv/Pa

### Features

- 1.Gray black elegant and graceful design, with modern fashion
- 2.Desktop is easy to move and install, even easy to increase or decrease microphone units
- 3.With voice control ability, the voice can turn on microphone, it does not need to press the microphone button by hand
- 4.With a big LCD display, it can show congressional information and status of equipment
- 5.With hi-fi built-in loudspeaker, when microphone is turned on, the built-in loudspeaker closes automatically to avoid feedback.
- 6.One  $\Phi$  3.5mm stereo interface for earphone, and the volume can be adjusted
7. One  $\Phi$  3.5mm stereo interface for outside microphone
- 8.System with function of automatic restoration, support "PnP"(Plug-and Play)
- 9.Chairman unit has priority to speak, it can close/ temporarily muting the delegate unit
- 10.Super powers of anti-electromagnetic and mobile phone interference
- 11.Microphone rods can be taken down during the recess, easy to maintain
- 12.Humanization design. There is different length MIC rods to choose, it is suitable for different height attendances
- 13.Direction microphones with red indicator for turning on
- 14.Connect to camera can realize the function of camera auto-tracking

### Project

