

SAMCEN

Ideas For Communication

Fully Digital Flush-mounting Discussion Unit SCS-6001C SCS-6001D



Products picture



SCS-6001C



SCS-6001D

Features

1. Excellent metal wiredrawing craft, classic in black and streamlined faceplate
2. Small in size, low in weight, solid in quality, economical and practical, convenient to transport
3. With voice control ability, the voice can turn on microphone, it does not need to press the microphone button by hand
4. Flush in installation, microphone rods can be taken down during the recess, it is nothing influence to the table top
5. Pluggable and lock line microphone rods, it can be adjust the direction freely
6. Bring 2.1 meters dedicated cable, increased reliability with "hand in hand" connection topology
7. System with function of automatic restoration, support "PnP" (Plug-and Play)
8. Chairman unit has priority to speak, it can close/ temporarily muting the delegate unit
9. Super powers of anti-electromagnetic and mobile phone interference
10. Microphone rods can be taken down during the recess, easy to maintain
11. Humanization design. There is different length MIC rods to choose, it is suitable for different height attendances
12. Connect to camera can realize the function of camera auto-tracking

Specifications

Model	SCS-6001C/D
Power supply	DC24V supplied by the control host
Intercommunication	DIN 8-pole
Power consumption	3W
Loudspeaker power	1.2W
Transducer type	Electret condenser
Directional pattern	Cardioid
SNR	> 80dB
Crosstalk attenuation	at 1k Hz > 80dB
Distortion	<0.10%
Frequency response	60~12KHz
Equivalent noise	≈20dB SPL
Maximum SPL	105dB(3% threshold)
Sensitivity	-22dBv/Pa

Project

