

SAMCEN

Ideas For Communication

Fully Digital Discussion Unit

SCS-6030C SCS-6030D



Products picture



SCS-6030C

SCS-6030D

Features

- .Working with SCS-6100MA controller, provide system expansion up to 120 delegate units, can expand to 2000 delegate unites at most by working expansion host.
 - .Indirection at microphone with red ting indicator.
 - .The integrated loud speaker will automatically mute to avoid howling when the microphone turns on.
 - .The active microphone can be limited in different numbers by setting in the front panel.
 - .Communicating in the hand-in-hand daisy-chain, easy installation and maintenance.
 - .Working with the control system to realize the function of camera auto-tracking.
 - .Voice Control: When the controller switched to voice control, the MIC can open ON automatic while the speaker begin to speak.
 - .Working with the control system to realize the function of camera auto-tracking.
- 160 X32mm LCD display screen menu of Chinese and English

Specifications

Model	SCS-6030C/D
Power supply	DC24V supplied by the control host
Intercommunication	DIN 8-pole
Power consumption	3W
Loudspeaker power	1.2W
Transducer type	Electret condenser
Directional pattern	Cardioid
SNR	> 80dB
Crosstalk attenuation	at 1k Hz > 80dB
Distortion	<0.10%
Frequency response	60~12KHz
Equivalent noise	≈20dB SPL
Maximum SPL	105dB(3% threshold)
Sensitivity	-22dBV/Pa

Project



Connection diagram

