

# SAMCEN

*Ideas For Communication*

## Fully Digital Discussion Unit

SCS-6040C SCS-6040D



### Products picture



SCS-6040C

SCS-6040D

### Specifications

Model	SCS-6040C/D
Power supply	DC24V supplied by the control host
Intercommunication	DIN 8-pole
Power consumption	3W
Loudspeaker power	1.2W
Transducer type	Electret condenser
Directional pattern	Cardioid
SNR	> 80dB
Crosstalk attenuation	at 1k Hz > 80dB
Distortion	<0.10%
Frequency response	60~12KHz
Equivalent noise	≈20dB SPL
Maximum SPL	105dB(3% threshold)
Sensitivity	-22dBv/Pa

### Features

1. Fine silvery white concise appearance design meets the ergonomics, has great fashion sense
2. Small in size, convenient to move and rental service
3. With voice control ability, the voice can turn on microphone, it does not need to press the microphone button by hand
4. Increased reliability with "Closed Loop-Daisy chain" (Hand in Hand) connection topology. The system has a higher safety and reliability
5. System can auto-fix automatically, supports Plug & Play
6. Super powers of anti-electromagnetic and mobile phone interference
7. Microphone rods can be taken down during the recess, easy to maintain
8. Super powers of anti-electromagnetic and mobile phone interference
9. Can reduce the feedback of the howling effective
10. Directional microphones with red indicator for turning on
11. Connect to camera can realize the function of camera auto-tracking

### Project

