

SAMCEN

Ideas For Communication

Fully Digital Flush-mounting Discussion Unit SCS-6070C SCS-6070D



Products picture



SCS-6070C

SCS-6070D


Features

1. With its artistic, taste and streamline design, able to fused together with any conference room
2. Using the metal wiredrawing craft, makes it strong and durable, it seems on quite the scale
3. Flush installation makes the meeting table more clean and tidy, presents rigorous and visual effect
4. With voice control ability, the voice can turn on microphone, it does not need to press the microphone button by hand
5. Condenser MIC core, with two colors indicator
6. Power supply from main unit, 24V safety voltage input
7. Built-in loudspeaker, earphone interface and volume adjustment button (when the microphone startup, the built-in loudspeaker will closes automatically)
8. Bring 2.1 meters dedicated cable, increased reliability with "hand in hand" connection topology
9. System with function of automatic restoration, support "PnP" (Plug-and Play)
10. Chairman unit has priority to speak, it can close/ temporarily muting the delegate unit
11. Super powers of anti-electromagnetic and mobile phone interference
12. Microphone rods can be taken down during the recess, easy to maintain
13. Humanization design. There is different length MIC rods to choose, it is suitable for different height attendances
14. LCD display shows congressional information and status of equipment Connect to camera can realize the function of camera auto-tracking

Specifications

Model	SCS-6070C/D
Power supply	DC24V supplied by the control host
Intercommunication	DIN 8-pole
Power consumption	3W
Loudspeaker power	1.2W
Transducer type	Electret condenser
Directional pattern	Cardioid
SNR	> 80dB
Crosstalk attenuation	at 1k Hz > 80dB
Distortion	<0.10%
Frequency response	60~12KHz
Equivalent noise	≈20dB SPL
Maximum SPL	105dB(3% threshold)
Sensitivity	-22dBv/Pa

Project



Open hole size

Product size (mm)

