

SAMCEN

Ideas For Communication

HD Conference Camera SCS-680HD



Products picture



SCS-680HD

Specifications

Monitor	Manual / time start-up setting
Preset speed	Pan 160°/s, Tilt 120°/s
Orientation precision	± 0.05°
Rotation	Pan ± 170°; Tilt -30° ~ + 90°
Speed Proportion	Auto-adjust the speed as the length of focus
Preset	Controller support 9 presets, RS232 support 255 presets
Sync	Internal
Decoder	Built-in
Video output	RCA , S terminal
Remote controlling	RS422/232
Baud rate(RS485)	9600bps
Temperature	-10℃ ~ +50℃
Humidity	0~95% (Non-condensation)
Dimension (L*W*H)	138 * 138 * 163 mm
Power supply	DC 12V ± 1V
Power consumption	12W
Weight	1.2kg

Features

- .Built-in zoom camera and decoder, integrated structure, smart outline, Pan: ± 170°, Tilt: - 30° ~ + 90°
- .Support YPbPr and HDMI Video Output
- .Max. pan speed: 160°/s; Max. Tilt speed: 120°/s
- .Support up to 255 presets
- .Communications:RS232/RS422, Infrared remote-controlling .Protocol: VISCA
- .Image flip function (decided by camera module)
- .Multifunctional IR remote controller
- .Support terminals of video conference camera from other manufacturers
- .Support top-down mounting

Project

