

SAMCEN

Ideas For Communication

HD Conference Camera SCS-690HD



Products picture



SCS-690HD

Specifications

Imaging element	1/3" HD COMS
Significant pixel (H×V)	752(H)×582(V)
Resolution	1080i/720p
Video output	YPbPr, 1.0±0.2Vp-p, BNC
S/N ratio (S/N)	≥50dB
Illumination	3Lux(F1.4)
White balance	Auto/manual (R/B gain control)
Back-compensation	Off/auto
Focus	5.1mm ~ 51mm
Electron Shutter	1/2 ~ 1/10,000 s
Manual speed	Pan (0.5°~160°/s) ; Tilt (0.5°~90°/s)
Preset speed	320°/s
Rotation	Continuously 360°; tilt 0~90° with auto-flip
Speed Proportion	As the length of focus, to auto-adjust the speed
Zoom	Total zoom 120X (Optical 10X; Digital 12X)
Preset	128 preset, title can be edited
Auto-flip	Tilt down 90°, with auto-flip 180°
Display zone	8 programmable zones with titles
Sync model	Internal
Decoder	Built-in
Remote controlling	RS485
Baud rate (RS485)	2400 / 4800 / 9600/19200 bps
ID range	1~254
Temperature	-30℃ ~ 50℃
Humidity	0~95% (No condensation)
Protection grade	IP66, 1500w lightning-proof, surge-proof, all-day defend cover
Power supply	AC 24V
Power consumption	< 12W
weight	2.5Kg
Dome Dimension (L*W*H)	154X154X152.6 mm

Features

- . Integrated and handle fast installation
- . Support YPbPr Video Output
- . Built-in heating and radiating system, four alarms input, one alarm output as factory default, IP board is optional.
- . Built-in zoom with 120 times(10x optical, 12x digital).
- . Resolutions: 1080i/720p; Min Illumination: color 3Lux.
- . Pan 360°, Tilt 90° continuously rotation with auto-flip, humanize focus and speed proportion.
- . 128 presets(titles can be set), 4 tours; 8 programmable zones(titles can be set)
- . Park action function, can auto-call presets or start-up tour, pattern, scan and display areas after dome is idle for a period of time.
- . Screen will display pan/ tilt position, zoom etc.
- . Communications: RS485
- . IP66 all-day defend cover.
- . Built-in TVS1500W lightning-proof, surge-proof and wave-proof.

Project

