SAMCEN

Ideas For Communication

Power Amplifier SCSGX7



Products picture



SCSGX7

Features

- . Power levels matched to the most popular speakers used by entertainers
- . Optimized for maximum real-world headroom into 4 ohm and 8 ohm speaker systems
- . Inputs: XLR, 1/4" TRS and phono input connectors for compatibility with any source Outputs: combo accepts, 1/4" (TS) plugs or Speakon 2-pole and 4-pole plugs (connects 2 poles only).
- . Binding posts support all other speaker wiring systems
- . Minimum depth chassis (10.1"/257 mm) fits in compact, inexpensive effects racks
- . Detente gain controls for precise setting and matching of sensitivity automatically protects the amplifier and loudspeakers from damage due to temperature rise or overdrive without shutting down the show
- .Front panel LEDs monitor Power, Signal and Clipping
- . Subwoofer/Satellite crossover built-in

Specifications

| Model | GX7 |
|----------------------|--|
| Output Power(8Ω) | 250W |
| Output Power(8Ω) | 350W |
| Bridge Mono Mode(8Ω) | 450W |
| Bridge Mono Mode(4Ω) | 600W |
| THD | 0.05% |
| Frequency Response | 20Hz-20KHz |
| S/N Ratio | 103dB |
| Weight | 7kg |
| Height | 2U |
| Cooling Mode | High/Low Automatism Cortrlo |
| Protection | DC safeguard/orerloading/startup boot/strap short test |

Project











