

SAMCEN

Ideas For Communication

Power Amplifier SCSGX8



Products picture



SCSGX8

Features

- . Power levels matched to the most popular speakers used by entertainers
- . Optimized for maximum real-world headroom into 4 ohm and 8 ohm speaker systems
- . Inputs: XLR, 1/4" TRS and phono input connectors for compatibility with any source Outputs: combo accepts, 1/4" (TS) plugs or Speakon 2-pole and 4-pole plugs (connects 2 poles only).
- . Binding posts support all other speaker wiring systems
- . Minimum depth chassis (10.1"/257 mm) fits in compact, inexpensive effects racks
- . Detente gain controls for precise setting and matching of sensitivity automatically protects the amplifier and loudspeakers from damage due to temperature rise or overdrive without shutting down the show
- . Front panel LEDs monitor Power, Signal and Clipping
- . Subwoofer/Satellite crossover built-in

Specifications

Model	GX8
Stereo Power(8Ω)	350W
Stereo Power(8Ω)	450W
BTL(8Ω)	600W
BTL(4Ω)	800W
THD	<0.05%
Frequency Response	20Hz-20KHz
S/N Ratio	103dB
Weight	7kg
Height	2U
Cooling Mode	High/Low Automatism Control
Protection	DC safeguard/overloading/startup boot/strap short test

Project

