

SAMCEN

Ideas For Communication

Keyboard Controller SCS-KB500



Products picture



SCS-KB500

Specifications

Joystick	4-axis, zoom function, shuttle, jog in the knob, auto returning
Buttons	28, multifunction, silicon + key stroke
Display	LCD, 2 lines of 20 characters, backlight
Dimensions	355(L) × 150(W) × 155(H)mm
Weight:	1.47kg (w/o Power supply); 1.89 kg (with Power supply); 2.4kg (prepared for shipping)
Operating Temperature	-10°C - 70°C
Humidity	30% - 90% (w/o condensation)
Adapter	DC12V / 1000mA
Power source	12 VDC
Power consumption	2.7 W (not loaded line)
Recommended adapter	AC100-240V-12VDC/1000mA
Connectors:	1 x RJ-45 (RS-485) (for digital video recorders)
	RS485(COM1)RS485 power output. 2000M(for camera)
	RS485(COM2)RS485 two-way communication. standard 485 main line, 1200M(for camera)
USB-D	USB2.0(for computer)

Features

SCS-KB500 Support Perco D/ P ,VISCA RS-422/RS485 protocol communication high speed long distance communication control. RS422/485 communication interface, longer distance Max 2000m. Preset 6-16 camera like pan control lens position white balance imagepause.

Project

